

Cabot's Exterior Varnish Stain Gloss

AUDW0663

Part A	525-Line
---------------	----------

Description

Cabot's Exterior Varnish Stain is a combined semi transparent stain and varnish that provides protection, colour and shine without hiding the grain. As it is water based, it is fast drying, so you can recoat after only 2 hours, and clean up is easy with water. Cabot's Exterior Varnish Stain is designed for use on exterior doors, windows, trim and outdoor furniture.

- Features**
- Superior 3 coat system.
 - UV protection.
 - Dirt and mould resistant.
 - High durability.
 - Fast recoat.

- Benefits**
- The exterior durable technology means only 3 coats are required as opposed to 5 or more coats which may be needed for other preproducts.
 - Blocks out harmful UV rays preventing them from penetrating and damaging the surface while resisting colour fading.
 - Contains powerful ingredients to resist the growth of wood staining mould while the unique formula provides excellent dirt and stain resistance.
 - Provides resistance to weathering and excellent gloss retention.
 - Recoat after only 2 hours.

Uses


Exterior new and weathered timber. Also suitable for pre-primed fibre cement products such as woodgrain Hardiplank (TM) and Primeline(R) weatherboards.

Precautions And Limitations

Do not apply this product in temperatures below 10°C or above 35°C, or when rain or heavy dew is expected during the drying period. In hot temperatures, do not apply in direct sunlight, cool the timber by lightly dampening with water and coat in the shade. Not suitable for use on walk-on areas.

Performance Guide

Weather	Formulated for exterior use	Salt	Unaffected by splash and spillage
Heat Resistance	Up to 70 degrees Celsius. Higher temperatures will cause film to soften.	Water	Excellent water resistance
Solvent	Sensitive to alcohol and hydrocarbon	Abrasion	Moderate resistance to abrasion
Acid	Suitable for splash (dilute only)	Alkali	Suitable for splash (dilute only)

Typical Properties																											
Gloss Level	Gloss	Colour	3 packaged colours + tinted colours																								
Components	1	Number Of Coats	3																								
Toxicity	Lead free. Dry film is non-toxic and conforms to AS1647, Part 3	V.O.C. Level	< 75g/L																								
Touch Dry	30 minutes																										
Clean Up	 Water																										
Application Method	  Air Spray Brush																										
Application Conditions	<table border="0" style="width: 100%;"> <tr> <td style="text-align: center;">Solids By Volume</td> <td style="text-align: center;">37</td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">Min</td> <td style="text-align: center;">Max</td> <td style="text-align: center;">Recommended</td> </tr> <tr> <td>Wet Film Per Coat (microns)</td> <td></td> <td></td> <td style="text-align: center;">84</td> </tr> <tr> <td>Dry Film Per Coat (microns)</td> <td></td> <td></td> <td style="text-align: center;">31</td> </tr> <tr> <td>Recoat Time (min)</td> <td colspan="2" style="text-align: center;">2 hours</td> <td></td> </tr> <tr> <td>Theoretical Spread Rate (m²/L)</td> <td></td> <td></td> <td style="text-align: center;">12</td> </tr> </table>			Solids By Volume	37				Min	Max	Recommended	Wet Film Per Coat (microns)			84	Dry Film Per Coat (microns)			31	Recoat Time (min)	2 hours			Theoretical Spread Rate (m²/L)			12
Solids By Volume	37																										
	Min	Max	Recommended																								
Wet Film Per Coat (microns)			84																								
Dry Film Per Coat (microns)			31																								
Recoat Time (min)	2 hours																										
Theoretical Spread Rate (m²/L)			12																								
Typical Properties Notes	SPREADING RATE Approximately 12 square metres per litre depending on the porosity and condition of the timber. DRYING AND RECOAT TIME All timings quoted at 25C and 50% humidity. Cooler or humid conditions may require longer.																										

Application Guide	
Surface Preparation	<ul style="list-style-type: none"> ▪ Note: Fill holes and imperfections with a suitable timber putty if required. <p>BARE TIMBER To coat new bare timber immediately, scrub damp timber with Cabot's New Timber Prep, following label instructions. New Timber Prep will draw out tannins and oils quickly from the surface, allowing you to skip the 4-6 weeks weathering process required for new timber. Always follow New Timber Prep with Cabot's Deck Clean following label instructions.</p> <p>PREVIOUSLY PAINTED OR VARNISHED TIMBER Remove back to bare timber using a paint stripper, or sanding. For exterior surfaces, then clean with Cabot's Deck Clean following label instructions.</p> <p>PREVIOUSLY STAINED AND OILED TIMBER For exterior surfaces, clean with Cabot's Deck Clean following label instructions, then allow timber to fully dry. Test if the surface is ready for coating by sprinkling water on the timber. If the water beads on the surface, repeat the application of Cabot's Deck Clean. If water is absorbed into timber, it is ready for coating. For a more transparent look, sand timber back to bare before coating.</p> <p>WEATHERED AND GREY TIMBER For best results, sand timber back to fresh substrate. Clean with Cabot's Deck Clean following label instructions.</p> <p>FIBRE CEMENT PRODUCTS SUCH AS HARDIEPLANK(TM) For a timber effect on fibre cement products such as woodgrain HardiePlank(TM) and PrimeLine® Weatherboards, prepare fibre cement boards by cleaning, and then coating with Cabot's Timbercolour in a pastel shade.</p>
Application Procedure And Equipment	<ul style="list-style-type: none"> ▪ Stir thoroughly with a broad flat paddle before and during use. Apply liberally along the full length of the board including exposed edges and end grain by brush. The initial milky colour helps with even product application, drying to a semi-transparent finish. Apply three coats, allowing a minimum of 2 hours drying between coats. <p>Leave doors and windows ajar while drying to avoid sticking. Avoid surface contact for several days to allow full curing.</p> <p>MAINTENANCE Regular inspection of all coated surfaces is recommended. When recoating aged Exterior Varnish Stain, if in good condition, lightly sand and clean surfaces, then apply one or more additional coats. If the coating is in poor condition, thoroughly strip off the existing coating and prepare as for new bare timber.</p>

Health And Safety			
MSDS Number	14545068	Using Safety Precautions	Provide adequate ventilation. If using indoors keep windows and doors open during use and while drying.
Health Effects	For advice contact a Doctor or Poisons Information Centre AUST 131 126, NZ 0800 764 766 SWALLOWED: Give plenty of water to drink. Seek medical advice. EYE: Rinse with plenty of running water. Seek medical help if irritation occurs. For further information or a copy of the Product Safety Data Sheet telephone Cabot's Customer Service Department on AUST 1800 011 006, NZ 0800 222 687. For emergencies phone AUST 1800 033 111, NZ 0800 734 607	Flammability	This product is non-flammable
Protective Equipment	Wear eye protection, protective clothing and gloves, and if spraying, wear a respirator with a combined vapour/particulate cartridge.	Storage	Keep out of reach of children.
Disposal	Do not pour leftover paint down the drain. Unwanted paint should be brushed out on newspaper, allowed to dry and then disposed of via domestic waste collections. Empty paint containers should be left open in a well ventilated area to dry out. When dry, recycle the container via steel can recycling programs. Disposal of empty paint containers via domestic recycling programs may differ between local authorities. Check with your local council first.		
In the case of emergency, please call 1800 033 111			

Transport And Storage	
Pack A	525-Line
Size 4L 2L 1L 500ml	Weight 4.5Kg 2.4Kg 1.2Kg 0.6Kg

Disclaimer

Dulux, Selleys and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating/product systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (Australia) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating/product systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Selleys" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of DuluxGroup (Australia) Pty Ltd ABN 67 000 049 427. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (Australia) Pty Ltd 1956 Dandenong Road, Clayton, Victoria 3168 AU ABN 67 000 049 427