

Cabot's Timbercolour Deck & Exterior Paint

AU_DW02256

Part A	540-line
---------------	----------

Description

Cabot's Timbercolour Deck & Exterior r Paint is a premium acrylic self priming exterior paint specifically formulated to provide exceptional durability to all exterior timber surfaces and decking. Its unique formula nourishes and protects the timber while providing excellent dirt and stain resistance.

- Features**
- Self priming
 - Mould and fungi resistant
 - Suitable for walk on surfaces
 - UV protection
 - Easy to apply
 - Low sheen solid colour finish

Uses






Exterior projects including weatherboard, garden furniture, decks, pergolas, fences and window frames. Also suitable for brick and masonry.

Precautions And Limitations

Temperature must be above 10°C during application and drying time. Do not apply if rain is expected during the drying period. In summer, hot windy conditions may necessitate painting on the cooler, shaded part of the project.

Performance Guide

Weather	Excellent.	Salt	Resists salt spray.
Heat Resistance	Up to 70 degrees Celsius. Higher temperatures will cause film to soften.	Water	Excellent.
Abrasion	Good.		

Typical Properties																											
Gloss Level	5-20% measured at 60 degrees	Thinner	Water																								
Colour	Timbercolour Deck & Exterior Paint can be tinted to a large range of colours.	Number Of Coats	2-3																								
V.O.C. Level	< 50g/L	Meets GBCA VOC Requirement?	Yes. Total Volatile Organic Content (TVOC) values are calculated in accordance to the stated methodology within Green Star Technical Manuals. The TVOC content is theoretically calculated as the sum total of the known VOC values of the product's raw material components. These materials include the base paint plus additional low VOC tinter required for non-factory packaged colours.																								
Touch Dry	30 minutes																										
Clean Up	 Water																										
Application Method	    Air Spray Airless Spray Brush Roller																										
Application Conditions	<table border="0" style="width: 100%;"> <tr> <td style="text-align: center;">Solids By Volume</td> <td style="text-align: center;">36</td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">Min</td> <td style="text-align: center;">Max</td> <td style="text-align: center;">Recommended</td> </tr> <tr> <td>Wet Film Per Coat (microns)</td> <td></td> <td></td> <td style="text-align: center;">64</td> </tr> <tr> <td>Dry Film Per Coat (microns)</td> <td></td> <td></td> <td style="text-align: center;">23</td> </tr> <tr> <td>Recoat Time (min)</td> <td colspan="2" style="text-align: center;">2 hours</td> <td></td> </tr> <tr> <td>Theoretical Spread Rate (m²/L)</td> <td></td> <td></td> <td style="text-align: center;">16</td> </tr> </table>			Solids By Volume	36				Min	Max	Recommended	Wet Film Per Coat (microns)			64	Dry Film Per Coat (microns)			23	Recoat Time (min)	2 hours			Theoretical Spread Rate (m²/L)			16
Solids By Volume	36																										
	Min	Max	Recommended																								
Wet Film Per Coat (microns)			64																								
Dry Film Per Coat (microns)			23																								
Recoat Time (min)	2 hours																										
Theoretical Spread Rate (m²/L)			16																								
Typical Properties Notes	<p>COVERAGE Approximately 16m²/L, depending on the porosity of the timber. Note: The first coat on porous and rough sawn timbers will require more coating than subsequent coats.</p> <p>DRY TIMES All timings quoted at 25°C and 50% relative humidity. Cold or humid conditions may require longer. Touch dry : 30 minutes. Recoat : 2 hours minimum.</p> <p>May be subjected to light foot traffic 24 hours after final coat. Normal foot traffic after 72 hours. Wait for 7 days before replacing furniture and rugs. Full cure in 7 days.</p>																										

Application Guide	
Surface Preparation	<ul style="list-style-type: none"> ▪ NEW TIMBER Allow new timber to weather for 4-6 weeks. Following label directions, clean with Cabot's Deck Clean to remove dirt, mildew, oil, wax and tannins. Heavy deposits of grease or wax should be removed first with mineral turpentine. WEATHERED TIMBER Fill any cracks or holes with a suitable filler. Sand all surfaces to a flat finish and remove greyed timber. Dust off and wash with Cabot's Deck Clean. PRE-PRIMED TIMBER & PAINTED SURFACES Test if surface is sound¹. If not, scrape off all loose and flaking paint. Fill any cracks or holes with a suitable filler. Sand all surfaces to a flat finish and remove greyed timber. Dust off. BRICK, MASONRY, FIBRO & FIBRE CEMENT BOARD Unpainted masonry surfaces should be cured for 28 days before painting. Ensure surface is sound¹ and clear of any loose sand or cement. Fill holes with grouting cement. Wash down with water using a stiff brush to remove all loose material. To remove any efflorescence (white salts) wipe down with a 5% solution of acetic acid (white vinegar). Hose down & allow to dry. Wash with a bleach solution and/or demossing chemical to remove mould, or moss. Then hose down. For further information on any preparation call 1800 011 006. ¹Ensure surface is sound by cutting a small X through the existing paint with a sharp blade, press cellulose tape firmly across the cut and then rip off the tape. If the paint comes off, it is unsound and should be removed. Repeat at random in a number of areas, to test the surface.
Application Procedure And Equipment	<ul style="list-style-type: none"> ▪ Stir thoroughly with a broad flat paddle before and during use. Apply by brush, roller or spray. When spraying, always backbrush immediately after each section is coated, to ensure a uniform finish. Apply two generous coats of Cabot's Timbercolour Deck & Exterior Paint. Apply three coats on all unpainted timber. Some colours may require more than the recommended number of coats to achieve full opacity. Take particular care to seal the end grain. THINNING: In hot conditions or highly absorbent surfaces, thin the coat with up to 10% water. +REGULAR MAINTENANCE Durability on horizontal surfaces will depend on wear and weather. Colour fading may occur in areas exposed to heavy foot traffic or excessive weather. Reapply coating as colour changes or as water resistance diminishes. Follow surface preparation instructions. As a guide, it is recommended to conduct a routine maintenance inspection and recoat as soon as the coating shows signs of deterioration. Additional maintenance may be required for extreme conditions.

Health And Safety			
Using Safety Precautions	Keep out of reach of children. Avoid contact with skin and eyes or breathing vapour. Wear waterproof gloves and safety glasses. Use only in well ventilated areas. Wash hands after use.	Health Effects	If poisoning occurs, contact a Doctor or Poisons Information Centre (AUST: 131 126; NZ 0800 764 766). SWALLOWED: Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water. EYE: If in eyes, hold eyes open, flush with running water for at least 15 minutes. SKIN: If skin contact occurs, remove contaminated clothing and wash skin thoroughly. INHALED: Remove from contaminated area. For further information or a copy of the Product Safety Data Sheet telephone Cabot's Customer Service Department on AUST 1800 011 006, NZ 0800 222 687. For emergencies phone AUST 1800 033 111, NZ 0800 734 607.
Flammability	This product is non-flammable.	Protective Equipment	Wear waterproof gloves and safety glasses.
Storage	Keep out of reach of children.	Disposal	Do not pour leftover product down the drain. Unwanted product should be brushed out on newspaper, allowed to dry and then disposed of via domestic waste collections. Empty paint containers should be left open in a well ventilated area to dry out. When dry, recycle the container via steel can recycling programs. Disposal of empty paint containers via domestic recycling programs may differ between local authorities. Check with your local council first.
Other	DO NOT REUSE CONTAINER.		
In the case of emergency, please call 1800 033 111			

Transport And Storage	
Pack A	540-line
Size	Weight
500ml	0.79kg
2L	3.03kg
4L	5.96kg
10L	14.72kg

Disclaimer

Dulux, Selleys and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating/product systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (Australia) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating/product systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Selleys" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of DuluxGroup (Australia) Pty Ltd ABN 67 000 049 427. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (Australia) Pty Ltd 1956 Dandenong Road, Clayton, Victoria 3168 AU ABN 67 000 049 427